

099 DISPERSION PRIMER

Primer for wall and floor.



Product Typification

Basis : Acrylic dispersion.

Colour : Light pink.

- Very low VOC-emission
- Emission EC 1 plus
- Non-flammable
- User friendly
- Favourable spreading capacity
- Multi-purpose application
- High penetration capacity
- For in- and outdoor use

Performances

Aging : 099 Dispersion Primer does not deteriorate with age.

Alkali resistance : 099 Dispersion Primer is resistant against alkaline moisture.

Classification : Emission EC 1 plus tested conform EN 13999-2/4.

Consumption : 6 - 9 m² per kg.

Specific weight : 1.0 kg/l.

Application

Primer for:

- improving the adhesion of sealants, tile adhesives and levelling compounds on absorbent gypsum or cement-based walls and floors, sheet material etc. Not suitable for impervious subfloors. Use 051 Europrimer Quartz.
- improving the top layer of cement screeds that tend to crumble on the surface.

Working Process

Storage : Store free from frost. Protect against high temperatures.

Tools : Lambswool roller, brush or spray-gun.

Drying : 1 - 2 hours, depending on temperature, relative humidity and subfloor.

Shelf Life : 12 Months, in unopened packaging. After use close the open packaging well.

Application temperature : From 5° to 25 °C (surrounding and subfloor temperature).

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- The subfloor should be clean, free from grease and dirt, dry and have a good tensile and compression strength, according to the requirements of DIN 18 353 and DIN 18 365.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

- Apply 099 Dispersion Primer thinly and evenly with a brush and/or lambswool roller.
- 099 Dispersion Primer can also be sprayed.
- Drying time 1 - 2 hours.
- Sandpaper old adhesive residues carefully and make dust-free.
- When installing tiles with 725 Alphycol on anhydrite floors keep a drying time of approx. 1 hour.
- Spreading capacity 100 - 150 g/m².

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

Quality and guarantee



Environment and health

Safety and environment : Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.
MSDS : For extensive information about safety and environment we refer to our website www.eurocol.nl.

DUBO:

Articles

Article	Definition	Packaging	EAN-code
099	Dispersion Primer	10 kg jerry can	8 710345 056502
099	Dispersion Primer	Box of 12 cans of 1 kg	8 710345 099035
099	Dispersion Primer	1 kg bottle	8 710345 056519