

905 EUROPLAN FILL

Universal fast drying repair mortar for floor.



Product Typification

Basis : Cement-based powder with additives.
Colour : Grey.
Consistency : Powder.

- Simple in use
- fast drying
- Applicable from 0 mm
- Very smooth finishing
- Directly usable

Performances

Consumption : Depends on type of repair.
Flammability : Non-flammable.

Application

Mortar for:

- smoothening away irregularities and differences of height in levelling and stony floors
- filling of joints of water-resistant sheet material, bitumen and tile floors
- repairing damaged concrete

Working Process

Storage : Store cool and dry.
Tools : Trowel or putty-knife.
Mixing ratio : Add 4 parts 905 Europlan Fill to 1 part of water or mix a small quantity of powder with water to a flexible mortar.
Processing time : Use within 5 minutes after mixing. *
Latency : None.
Drying : 15-30 minutes. *
Shelf Life : 12 months, in unopened packaging.

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- 905 Europlan Fill can be applied on any stony subfloor that is rigid and has a good tensile and compression strength. The subfloor should

also be clean, free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.

- Apply 044 Europrimer Multi thinly and evenly on smooth and impervious subfloors (tile floors, granito, terrazzo etc.).
- Porous cement screeds should first be damped with water or primed with 044 Europrimer Multi or 049 Europrimer ABS.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

- Add 4 parts of 905 Europlan Fill to 1 part of water and stir thoroughly to a homogeneous mixture.
- Apply the mortar immediately with a trowel or putty-knife.
- Until approx. 1 hour after hardening, the applied 905 Europlan Fill can still be polished by sprinkling the mortar with a little water and polishing it with a trowel.

Environment and health

Hazard Class : Xi (irritating).

Safety and environment : Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.

MSDS : Available on request.

Articles

Article	Definition	Packaging	EAN-code
905	Europlan Fill	Box with 4 kg bucket	8 710345 905107